

Panafax[®]
UF-9000

send it! print it!

- Super G3 Fax with JBIG
- Flatbed Color Scanner
- Scan-to-PC/Email
- Up to 19 ppm Print Speed
- Standard Duplex Printing
- Standard Network Printing/
Scanning/Document Management
- Digital SkyShot/Double Exposure



Panasonic ideas for life

Options

Flash Memory

- 4MB Flash Memory**
UE-410047F
- 8MB Flash Memory**
UE-410048F



Handset Kit


- Handset Kit**
UE-403171

Paper Feed Module/Stand

- 550-sheet 2nd Paper Feed Module**
DA-DS188



- Stand**
DA1D190



Printer/Network Printer

- Expansion F-ROM Board**
DA-EM600F

- PCL Printer Controller Module**
DA-PC190

- PS/PCL Multi Page Description Language Controller Module**
DA-MC190

Image Memory

- Image Memory**
(16MB) DA-SM16B
(64MB) DA-SM64B
(128MB) DA-SM28B

Hard Disk Drive Unit

- Hard Disk Drive Unit (40GB)**
DA-HD19

Software

- Accounting Software**
DA-WA10

Consumable



Toner Cartridge

UG-5530*

The all-in-one design includes the toner, developer and drum for easy replacement.

*Approximately 5K pages @ 5%.

UF-9000 Specifications

General

Type	Desktop
Warm-up time (from sleep mode)	Approximately 15 seconds
Power Requirements	AC 120V, 50/60Hz
Power Consumption	Maximum: 900 Wh Power saver mode: 20 Wh Sleep mode: 12 Wh
Dimensions (W x D x H)*1 (Excluding optional equipment)	18.2" x 19.9" x 20.6" (462 x 506 x 523 mm)
Weight*1 (Excluding consumable supplies and optional equipment)	Approximately 48.5 lb (22 kg)

Fax

Compatibility	ITU-T Group 3, ECM
Modem Speed	33.6 - 2.4 kbps with automatic fallback
Coding Scheme	MH/MR/MMR/JBIG
Transmission Speed*2	Approximately 2.7 seconds
Number of Memory Job Files	50
Document Size	Maximum: 8.5" x 78.7" (216 mm x 2,000 mm*) (with operator's assistance) Minimum: 5.8" x 5.0" (148 mm x 128 mm)
Effective Scanning Width	8.34" (212 mm)
Automatic Document Feeder	50 sheets (20 lb)
Scanning Speed	Approximately 2.7 sec./page (Letter)
Scanning Resolution	Standard: 203 dots/inch x 98 lines/inch (8 dots/mm x 3.85 lines/mm) Fine: 203 dots/inch x 196 lines/inch (8 dots/mm x 7.7 lines/mm) Super Fine: 406 dots/inch x 391 lines/inch (16 dots/mm x 15.4 lines/mm) 600 dpi: 600 dpi x 600 dpi
Recording Method	Monochrome laser printing on plain paper
Recording Paper Size	Letter/Legal
Effective Recording Width	8.15" (207mm)
Paper Feed	Standard Tray: 250 sheets Optional Paper Feed: 550 sheets
Image Memory Capacity	Standard: 2MB (120 pages)*4 Optional: Base memory plus 4MB (320 pages)*4/ 8MB (640 pages)*4
Number of Auto Dialers	200 Maximum: 1000 with optional Hard Disk Drive Unit

Digital Copier

Original Size	Letter/Legal/Invoice (LG: only using ADF)
Resolution	600 x 600 dpi
Zoom	50% - 200%
First Copy Time	Approximately 10 seconds
Multi Copy Speed	Up to 19 cpm*5 (Letter)
Copy size	Letter/Legal/Invoice*5
Exposure Controller	Text, Text/Photo, Photo
Sort Memory	Uses JBIG Compression
Standard	16MB
Optional	Base Memory (16MB) plus 16MB/64MB/128MB (max. 144MB) 12GB (with optional HDD)

Printer

Network Printer Interface	Ethernet 10Base-T/100Base-TX
Local Printer Interface	USB 1.1
Printing Speed	Up to 19 ppm*6
Paper Size	Letter/Legal/Invoice*5/Envelope*5
Printing Resolution	Maximum: 1200 equivalent x 600 dpi
Printer Memory	20MB
Standard Network Printing	Panasonic Printing System for Windows
Page Description Language (Option)	PCL 6 Emulation, Adobe® PostScript® 3™
Compatible Operating Systems	Windows® XP/2000/Me/98, Windows NT® 4.0 MAC OS 8.6-10.1 (PS only)

Scanner

Network Scanner Interface	Ethernet 10Base-T/100Base-TX
Communication Protocol	LPR, FTP
Scanning Speed / Resolution	Color: Approximately 11 sec./page (Letter) Standard: 75 x 75 dpi Fine: 150 x 150 dpi Super Fine: 300 x 300 dpi B/W: Approximately 2.7 sec./page (Letter) Standard: 150 x 150 dpi Fine: 300 x 300 dpi Super Fine: 600 x 600 dpi
Data Format	Color: JPEG, PDF B/W : Multi-page TIFF, PDF

Scan-to-Email / Internet Fax

Compatibility	IETF RFC 2305, ITU-T T.37
Communication Protocol	TCP/IP, SMTP, POP3, MIME, DHCP, LDAP, SNMP/MB
Network Connectivity	Ethernet 10Base-T/100Base-TX
Data Format*7	TIFF, PDF, JPEG

Dimensions



Notes

- *1 Dimensions and weight are approximate.
- *2 Transmission time applies to memory transmission of text data using only ITU-T Image No.1 between the same models at maximum modem speed. Transmission time may vary in actual usage. Usually public telephone lines can only support communication speeds of 28.8 Kbps or lower. Via PBX, transmission speed may fall back to a lower speed.
- *3 Standard/Fine mode
- *4 Based on ITU-T Image No.1 scanned in Standard mode.
- *5 Bypass only
- *6 Speeds are contingent upon applications, machine configuration and status; individual speeds may vary.
- *7 Internet Fax only supports TIFF format

Design and specifications are subject to change without notice. Not all options may be available at the time of notification.

Microsoft® Windows® and Windows NT® are registered trademarks of Microsoft Corporation. Adobe®, PostScript®, PostScript® 3™, PDF and PostScript logo® are trademarks of Adobe Systems, Inc. PCL is either a trademark or a registered trademark of Hewlett-Packard Company.



As an Energy Star® partner, Panasonic has determined that this product meets the Energy Star® guidelines for energy efficiency.



Panasonic Digital Document Company
Unit of Matsushita Electric Corporation of America

Two Panasonic Way, Secaucus, NJ 07094
For a local dealer, please call 1-800-742-8086
<http://www.panasonic.com/office>

ISO 9001 Quality Management System

Our business processes which produce document, information and network products, from manufacturing to marketing, conform to ISO9001 Quality Management Systems standard. Design, development, manufacture, installation, repair and maintenance of document, information and network products, their associated devices and consumables. In addition, the plants outside Japan have acquired ISO 9001 certification.

